

Project:

Date:

Catalog #:

Notes:

### Key Features & Benefits:


- Universal AC Input / Full Range (up to 305 VAC)
- Built-in Active PFC Function
- Protections: Short Circuit / Over Voltage / Over Temperature
- Suitable for Dry / Damp Locations
- Easy Installation with ESL Vision Quick Connect Series
- 7 Year Warranty



### Technical Specifications:

Input	Output	Environment
Input Voltage: 100 - 277 VAC	DC Voltage: 42 VDC	Working Temperature: -20 ~ 50°C
Power Factor: 0.98 / 120 VAC, 0.93 / 277 VAC	Rated Current: 380 mA	Max Case Temperature: 88°C
Total Harmonic Distortion: 15%	Rated Power: 36W	Working Humidity: 20 -70% RH
Frequency Range: 47~63Hz	Voltage Range: 28 - 42 VDC	
Efficiency: 89%	Line Regulation: 3%	
AC Current: .30 A / 120 VAC, .130 A / 277VAC	Load Regulation: 2%	

### Driver Dimensions:



Example Part Number: **ESL-DQC1-36W-1L**

<b>ESL</b>	-	<b>DQC1</b>	-	<b>30W</b>	-	<b>1L</b>
ESL		DRIVER		WATTS		DC OUTPUT
		DQC1		10W 18W 12W 22W 13W 30W 15W 36W		1L