

Key Features & Benefits:

- Rugged Die Cast Aluminum Housing:
 - Dark bronze polyester powder coat finish
- Optical Grade Polycarbonate Lens:
 - UV stabilized
 - Molded prismatic for optimal uniformity
 - Impact resistant
- Built-in 120V Photocell
- Continuous Gasket for Weather-Tight Seal
- LEDs Mounted to and Protected by Aluminum Housing with Easy Driver Access Hinged Door
- (3) 3/4" Threaded knockouts:
 - (1) On back
 - (1) On either side
- Suitable for Wet Locations
- 10 Year Limited Warranty
- Mounting Options:
 - Direct to electrical box
 - Flush wall mount

Project: _____ Date: _____



Catalog #: _____

Notes: _____



Technical Specifications:

- Power: 17 Watts
- Lumen Output: Up to 1,950 Lumens
- Efficacy (lm/W): Up to 115 Lumens per Watt
- Kelvin: 3000K, 4000K, 5000K
- CRI: >80
- Input Voltage: 120-277 VAC
- Life Span: 50,000 Hours
- Operating Temperature: -40°F - 104°F
- Dimensions (LxWxD): 5.48" x 8.38" x 3.52"



ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-WP-17W-330	17W	1,800	115	3000K
ESL-WP-17W-340	17W	1,900	112	4000K
ESL-WP-17W-350	17W	1,950	115	5000K

Ordering Guide:

ESL	-	WP	-	17W	-	3	-	
ESL		TYPE		WATTS		GENERATION		KELVIN*
		WP (Wall Pack)		17W		3 (3rd Generation)		30 (3000 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

* Other kelvin options available upon request