

Key Features & Benefits:


- High Quality Construction:
 - Rugged fiberglass 5(VA) rated housing
 - Highest rated flame retardant: UL94
 - Marine grade stainless steel latches and 316 mounting brackets come standard
 - Ideal for food and beverage processing facilities and other sanitary environments
- Lens:
 - Clear 100% impact modified acrylic
 - UV stabilized lens
 - Clear polycarbonate clips
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Built For Durability:
 - Rated UL wet location: IP67 high pressure washdown up to 1500PSI, NEMA 4X housing
 - High-Temperature silicon perimeter gasket
 - Suitable for corrosive environments
- Control Options:
 - Photocell
 - Occupancy
- Emergency capable
- Optional 0-10v Dimming
- 1/2" NPT / M20 fittings on both sides



Project: _____ Date: _____
 Catalog #: _____
 Notes: _____



Single Ti Normal Distribution



Electrical Data:

Light Specifications:

Lumen Output: Up to 2,175 Lumens
 Efficacy (lm/W): Up to 129 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 18W
 Input Current @ 120V: 0.15 Amps
 Input Current @ 240V: 0.075 Amps
 Input Current @ 277V: 0.065 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-TI-VP4S-S-18W-F30	18W	2,125	126	3000K	PYCYQMBU
ESL-TI-VP4S-S-18W-F35	18W	2,135	126	3500K	PZ31AQ5A
ESL-TI-VP4S-S-18W-F40	18W	2,150	127	4000K	PZWVO3XI
ESL-TI-VP4S-S-18W-F50	18W	2,175	129	5000K	PDJV9R14

Ordering Guide: Example Part Number: **ESL-TI-VP4S-S-18W-F30**

ESL	-	Ti	-	VP4S	-	S	-	18W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		VP4S (Slim)		S		18W (18 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Additional Options:

- ESL-CS3W-6* Cord Set, White, 3 wire, 6 foot
- ESL-CS3W-6P* Cord Set, White, 3 wire, 6 foot, Standard Plug
- ESL-CS3W-6TL* Cord Set, White, 3 wire, 6 foot, Twist lock Plug
- ESL-CS3W-12* Cord Set, White, 3 wire, 12 foot
- ESL-CS3W-12P* Cord Set, White, 3 wire, 12 foot, Standard Plug
- ESL-CS3W-12TL* Cord Set, White, 3 wire, 12 foot, Twist lock Plug
- ESL-SPD-277-1 Surge Protector; (100-277 VAC)
- ESL-480V-SD01 480 Volt Step Down Transformer
- ESL-4OCC-LDD Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
- ESL-REM-100 Remote for 2OCC-HDD, 3OCC/B, 4OCC-LDD, *OCC
- ESL-VP-CM-VP4S Direct Mount to the Ceiling (2 per) for the 4' single fixture
- ESL-VPSS Stainless Steel Latches (2'=6 latches) (4' =8 latches) (VPHB' =12 latches)

*Other lengths and black cord available upon request

Dimensions:

