

Key Features & Benefits:


- Quick Connect Technology
 - No need to worry about shunted or non-shunted tombstones
 - Extremely fast installation
 - No power though the pins
 - Power through the cord
- Interchangeable End Caps – Designed to Work With any Tombstone
 - G13 (Standard)
 - Fa8 (Single Pin)
 - R17D (HO)
- Long Life 80,000 Hours (L70)
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Universal Input 120-277V; 50/60Hz External Driver
- Glass Free
- Vibration and Impact Resistant
- No UV Emission
- Suitable for Dry and Damp Locations



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical Data:

Light Specifications:

Lumens Per Lamp: Up to 1,599 Lumens
 Efficacy (lm/W): Up to 123 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Triple Output
 Output Power: 13 Watts per Lamp (39 Watts Total)
 Input Current @ 120V: 0.325 Amps
 Input Current @ 240V: 0.163 Amps
 Input Current @ 277V: 0.141 Amps
 Total Harmonic Distortion (THD): <10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS PER LAMP	LUMENS PER LAMP	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-2-S-13W-3L-F30	13W	1,560	120	3000K	PEKXS1QB
ESL-Ti-2-S-13W-3L-F35	13W	1,560	120	3500K	PZ513N3Q
ESL-Ti-2-S-13W-3L-F40	13W	1,573	121	4000K	PUGZRZTW
ESL-Ti-2-S-13W-3L-F50	13W	1,599	123	5000K	PEJRQQ9T

Ordering Guide:

ESL	Ti	2	S	13W	3L	F	
ESL	TYPE	LENGTH	CLASS	WATTS	LAMP	LENS	KELVIN
	Ti Series	2 (Two Feet)	S	10W (10 Watts) 13W (13 Watts)	1L (One Lamp) 2L (Two Lamp) 3L (Three Lamp) 4L (Four Lamp)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Endcap Options:

ENDCAP
ESL-Ti-G13* ESL-Ti-Fa8 ESL-Ti-HO

*Standard endcap - Only DLC approved product

Alternate Ti Options:




1L Output

2L Output

4L Output

Dimensions:

Ti:



Driver:

