

Key Features & Benefits:


- Quick Connect Technology
 - No need to worry about shunted or non-shunted tombstones
 - Extremely fast installation
 - No power through the pins
 - Power through the cord
- Interchangeable End Caps – Designed to Work With any Tombstone
 - G13 (Standard)
 - Fa8 (Single Pin)
 - R17D (HO)
- Long Life 80,000 Hours (L70)
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Universal Input 120-277V; 50/60Hz External Driver
- Glass Free
- Vibration and Impact Resistant
- No UV Emission
- Suitable for Dry and Damp Locations



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical Data:

Light Specifications:

Lumens Per Lamp: Up to 2,376 Lumens
 Efficacy (lm/W): Up to 132 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Triple Output
 Output Power: 18 Watts per Lamp (54 Watts Total)
 Input Current @ 120V: 0.45 Amps
 Input Current @ 240V: 0.225 Amps
 Input Current @ 277V: 0.195 Amps
 Total Harmonic Distortion (THD): <10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS PER LAMP	LUMENS PER LAMP	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-4-S-18W-3L-F30	18W	2,304	128	3000K	PE599C8E
ESL-Ti-4-S-18W-3L-F35	18W	2,322	129	3500K	P1S6YPSA
ESL-Ti-4-S-18W-3L-F40	18W	2,340	130	4000K	PW8M9RY6
ESL-Ti-4-S-18W-3L-F50	18W	2,376	132	5000K	PSJS12BQ

Ordering Guide:

ESL	Ti	4	S	18W	3L	F	
ESL	TYPE	LENGTH	CLASS	WATTS	LAMP	LENS	KELVIN
	Ti Series	4 (Four Feet)	S	13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)	1L (One Lamp) 2L (Two Lamp) 3L (Three Lamp) 4L (Four Lamp)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Endcap Options:

ENDCAP
ESL-Ti-G13* ESL-Ti-Fa8 ESL-Ti-HO

*Standard endcap - Only DLC approved product

Alternate Ti Options:




1L Output

2L Output

4L Output

Dimensions:

Ti:



Driver:

