

### Key Features & Benefits:

- High Quality Construction:
  - Rugged fiberglass 5(VA) rated housing
  - Highest rated flame retardant: UL94
  - Marine grade stainless steel latches and 316 mounting brackets come standard
  - Ideal for food and beverage processing facilities and other sanitary environments
- Lens:
  - Clear 100% impact modified acrylic
  - UV stabilized lens
  - Clear polycarbonate clips
- Built For Durability:
  - Rated UL wet location: IP67 high pressure washdown up to 1500PSI, NEMA 4X housing
  - High-Temperature silicon perimeter gasket
  - Suitable for corrosive environments
- Control Options:
  - Occupancy
- 1/2" NPT / M20 fittings on both sides



Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:


#### Light Specifications:

Lumen Output: Up to 2,280 Lumens  
 Efficacy (lm/W): Up to 114 Lumens per Watt  
 Kelvin: 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 50,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 20W  
 Input Current @ 120V: 0.167 Amps  
 Input Current @ 240V: 0.083 Amps  
 Input Current @ 277V: 0.072 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Dual Tube Normal Distribution



### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-VP2N-S-20W-F35	20W	2,260	113	3500K
ESL-ID-VP2N-S-20W-F40	20W	2,260	113	4000K
ESL-ID-VP2N-S-20W-F50	20W	2,280	114	5000K

**Ordering Guide:**

<b>ESL</b>	-	<b>ID</b>	-	<b>VP2N</b>	-	<b>S</b>	-	<b>20W</b>	-	<b>F</b>	-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN
		ID Series		VP2N (Normal)		S		20W (20 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)
												OPTIONS

Example Part Number: ESL-ID-VP2N-S-20W-F35

**Options (Add as Suffix):**

ESL-4OCC-LDD  
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Remote for 2OCC-HDD, 3OCC/B, 4OCC-LDD, 8OCC

**Dimensions:**

