

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Zero Maintenance
- Superior Heat Management
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Optional 0-10v Dimmable

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Light Specifications:

Lumen Output: Up to 3,110 Lumens  
 Efficacy (lm/W): Up to 126 Lumens per Watt  
 Kelvin: 3,000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >80,000 Hours

### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 26W  
 Input Current @ 120V: 0.217 Amps  
 Input Current @ 240V: 0.108 Amps  
 Input Current @ 277V: 0.093 Amps  
 THD: <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F414-S-26W-F30	26W	2,825	113	3000K	PXK7PX90
ESL-Ti-F414-S-26W-F35	26W	2,990	115	3500K	PCRTZ5BC
ESL-Ti-F414-S-26W-F40	26W	3,068	118	4000K	PVVLH6LG
ESL-Ti-F414-S-26W-F50	26W	3,172	122	5000K	PP9K66WG

### Ordering Guide:

ESL	-	Ti	-	F414	-	S	-	26W	-	F	
ESL		TYPE		SERIES		LISTING		WATTS		LENS	KELVIN
		Ti Series		F414		S		26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)		F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Example Part Number: ESL-Ti-F414-S-26W-F30

### Dimensions:

