

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Zero Maintenance
- Superior Heat Management
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Optional 0-10v Dimmable

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Light Specifications:

Lumen Output: Up to 3,484 Lumens  
 Efficacy (lm/W): Up to 124 Lumens per Watt  
 Kelvin: 3,000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >80,000 Hours

### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 30W  
 Input Current @ 120V: 0.234 Amps  
 Input Current @ 240V: 0.117 Amps  
 Input Current @ 277V: 0.101 Amps  
 THD: <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F414-S-30W-F30	30W	3,330	111	3000K	PFQ4Q8Z5
ESL-Ti-F414-S-30W-F35	30W	3,390	113	3500K	PJ2S3O2F
ESL-Ti-F414-S-30W-F40	30W	3,450	115	4000K	PUFGYNJB
ESL-Ti-F414-S-30W-F50	30W	3,540	118	5000K	PIJK82EY

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>F414</b>	-	<b>S</b>	-	<b>30W</b>	-	<b>F</b>	-	
ESL		TYPE		SERIES		LISTING		WATTS		LENS		KELVIN
		Ti Series		F414		S		26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Example Part Number: ESL-Ti-F414-S-30W-F30

### Dimensions:

