

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 5,280 Lumens
 Efficacy (lm/W): Up to 120 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 44W
 Dimming: 0-10v
 Input Current @ 120V: 0.367 Amps
 Input Current @ 240V: 0.183 Amps
 Input Current @ 277V: 0.159 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

| ITEM# | WATTS | LUMEN OUTPUT | EFFICACY (lm/W) | KELVIN | DLC QPL CODE |
|-----------------------|-------|--------------|-----------------|--------|--------------|
| ESL-Ti-F314-S-44W-F30 | 44W | 4,928 | 112 | 3000K | P1EKVEZK |
| ESL-Ti-F314-S-44W-F35 | 44W | 5,016 | 114 | 3500K | P95HN2B4 |
| ESL-Ti-F314-S-44W-F40 | 44W | 5,104 | 116 | 4000K | PF7FBXXY |
| ESL-Ti-F314-S-44W-F50 | 44W | 5,280 | 120 | 5000K | P8JMS7YU |

Ordering Guide:

| | | | | | | | | | | | | | | |
|------------|---|-----------|---|-------------|---|----------|---|--|---|-------------|---|--|---|---------|
| ESL | - | Ti | - | F314 | - | S | - | 44W | - | F | - | | - | |
| ESL | | TYPE | | SERIES | | CLASS | | WATTS | | LENS | | KELVIN | | OPTIONS |
| | | Ti Series | | F314 | | S | | 26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts) | | F (Frosted) | | 30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin) | | |

Example Part Number: ESL-Ti-F314-S-44W-F30

Options (Add as Suffix):

- ESL-EMG-FDC-30W Emergency Back Up, DC, 30 Watt
- ESL-EMG-2DC-9W Emergency Back Up, DC, 9 Watt, External Battery
- ESL-4OCC-LDD Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
- ESL-REM-100 Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

