

## Easyfit Light Level Sensor

**Easyfit Light Level Sensor measures and reports the level of available natural light.**

**Used in conjunction with suitable controllers such as EnOcean LEDR and LEDD, it enables implementation of energy saving daylight harvesting control systems.**



Daylight harvesting is a great way to save energy and cost while enhancing worker satisfaction by allowing personal control of light levels.

Lighting control systems employing this technique measure natural light available in a building and only add as much artificial light as necessary.

### Functional Principle

EnOcean Light Level Sensor uses a solar cell both to measure the amount of available natural light and to generate the required energy for its operation.

Natural light level is measured every minute and significant changes (> 50 lux) are transmitted immediately. In addition, a heartbeat message containing the current light level is transmitted at random intervals between 20 ... 30 minutes.

EnOcean Light Level Sensor is interoperable with other devices using the EnOcean Wireless Standard.

EnOcean Light Level Sensor can be quickly deployed without wiring and is maintenance free thanks to the ability to harvest the energy required for operation.

EnOcean Light Level Sensor is optimized for operation together with the EnOcean LED Controllers LEDD and LEDR.

### Ordering Information

TYPE  
ELLSU (EnOcean 902 MHz)

ORDERING CODE  
ESL-ELLSU-W-EO

### Feature Overview

<b>Power supply</b>	Solar energy harvesting (integrated solar cell)
<b>Measurement range / resolution</b>	0 ... 1020 lux / 4 lux
<b>Typical accuracy</b>	+ -5 % at full scale / 68°F
<b>Measurement interval</b>	1 minute
<b>Transmission interval</b>	Immediate if change > 50lux versus last transmission Heartbeat every 20 ... 30 minutes (affected at random)
<b>Radio standard</b>	EnOcean 902 MHz
<b>Radio range</b>	80 ft. (25m)
<b>EnOcean Equipment Profile (EEP)</b>	A5-06-02
<b>Dimensions</b>	6.30" L x 2.36" W x 1.15" D (160 mm x 60 mm x 37 mm)
<b>Weight</b>	4.4 oz. (125 g)
<b>Mounting position</b>	At the ceiling, close to ambient light source (window)
<b>Operating conditions</b>	Indoor use only / 32° to 140° F (0° to 60° C) 20% to 85% relative humidity (non-condensing)
<b>Approvals</b>	FCC, IC, RoHS