



LED VAPOR TIGHT SERIES



ID - VP8N - 60 Watts

PAGE 1 OF 2

Key Features & Benefits:

- High Quality Construction:
 - Rugged fiberglass 5(VA) rated housing
 - Highest rated flame retardant: UL94
 - Marine grade stainless steel latches and 316 mounting brackets come standard
 - Ideal for food and beverage processing facilities and other sanitary environments
- Lens:
 - Clear 100% impact modified acrylic
 - UV stabilized lens
 - Clear polycarbonate clips
- Built For Durability:
 - Rated UL wet location: IP67 high pressure washdown up to 1500PSI, NEMA 4X housing
 - High-Temperature silicon perimeter gasket
 - Suitable for corrosive environments
- Control Options:
 - Occupancy
- 1/2" NPT / M20 fittings on both sides



Project: _____

Date: _____

Catalog #: _____

Notes: _____



Electrical Data:


Light Specifications:

Lumen Output: Up to 7,260 Lumens
 Efficacy (lm/W): Up to 121 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 50,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 60W
 Input Current @ 120V: 0.25 Amps
 Input Current @ 240V: 0.125 Amps
 Input Current @ 277V: 0.108 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Dual Tube Normal Distribution



Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-VP8N-S-60W-F35	60W	7,020	117	3500K
ESL-ID-VP8N-S-60W-F40	60W	7,140	119	4000K
ESL-ID-VP8N-S-60W-F50	60W	7,260	121	5000K

Ordering Guide:

ESL	ID	VP8N	S	60W	F		
ESL	TYPE	SERIES	CLASS	WATTS	LENS	KELVIN	OPTIONS
	ID Series	VP8N (Narrow)	S	60W (60 Watts)	F (Frosted)	35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	

Example Part Number: ESL-ID-VP8N-S-60W-F35

Options (Add as Suffix):

ESL-4OCC-LDD
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Remote for 2OCC-HDD, 3OCC/B, 4OCC-LDD, 8OCC

Dimensions:

