

Key Features & Benefits:

- Standard On/Off Control
- IP65 - Weather Resistant
- Built-In Surge Protector
- 120-277 VAC, HV 347-530 VAC



Project: _____

Date: _____

Catalog #: _____

Notes: _____

Technical Specifications:

Working Voltage: 120-277 VAC, HV - 347-530 VAC

Rated Loading: 1000W Tungsten, 1800VA Ballast

Power Consumption:

- PCOF: 0.5W (10 Amp)
- PCOFHV: 0.9W (20 Amp)

On/Off Level: 16 Lux On / 24 Lux Off

Ambient Temperature: -40 ~ 158°F(-40 ~ 70°C)

Related Humidity: 99%

Dimensions (ØxH):

- PCOF: 3.3" x 2.6"
- PCOFHV: 2.93" x 1.98"

Weight (lbs):

- PCOF: 0.24 lbs
- PCOFHV: 0.28 lbs



PCOF



PCOFHV

ITEM #	DESCRIPTION
ESL-PCOF	Standard on/off photocell - 120-277 VAC
ESL-PCOFHV	Standard on/off photocell - 347-530 VAC

Wiring Diagram:

Install the ESL-PCOF/HV with the photocell facing North (as indicated on top of housing). Adjust position if necessary in field.

