



LED VOLUMETRIC SERIES

SPECTRUM SERIES

Spectrum - 520 - 2x2 / 2x4

Key Features & Benefits:

- Bluetooth Mesh Network Enabled
- TAP Technology – NFC Programmable
- QR Code Programmable
- Tunable White Technology (3000K to 5000K)
- Wattage Adjustable
- 0-10v dim to off

Construction:

- Housing – Code-Gauge Cold-Rolled Steel
- Optics – Acrylic Lens

Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical and Light Specifications

- Input Voltage: 120-277 VAC
- Adjustable Power: 10-25 Watts, 25-45 Watts
- Input Current @ 120V: 0.102 Amps
- Input Current @ 240V: 0.051 Amps
- Input Current @ 277V: 0.044 Amps
- THD: <10%
- Power Factor:>0.99
- Operating Temperature: -4 ~ 122°F
- Kelvin Tunable (3000K to 5000K)
- Color Rendering Index (CRI): >82
- Rated Life: >80,000 Hours

KELVIN
TUNEABLE

ADJUSTABLE
WATTAGE

Ordering Guide:

Example Part Number: **ESL-SPE-520-24-2545W-3050K**

ESL	-	SPE	-	520	-		-	3050
ESL		SERIES		TYPE		LENGTH		WATTAGE
				520 (Volumetric)		22 (2x2) 24 (2x4)		1025 (10 to 25W) 2545 (25 to 45W)
								3050 (3000K to 5000K)

Catalog Data:

SERIES	LENGTH	WATTS	KELVIN LUMEN OUTPUT			
			3000K	3500K	4000K	5000K
520 - VOLUMETRIC - 1025W	2x2	10W	1,300	1,326	1,339	1,365
		15W	1,950	1,989	2,008	2,047
		25W	3,250	3,315	3,348	3,413
520 - VOLUMETRIC - 2545W	2x2	25W	3,250	3,315	3,348	3,413
	2x4	35W	4,550	4,641	4,687	4,778
		45W	5,850	5,967	6,026	6,143

Dimensions:

SERIES	L	H	DEPTH
520 - VOLUMETRIC - 2x2	23.8"	23.8"	3.6"
520 - VOLUMETRIC - 2x4	47.8"	23.8"	3.6"

