



LED FLAT PANEL SERIES

SPECTRUM SERIES

Spectrum - 521 - 1x4 / 2x2 / 2x4

Key Features & Benefits:

- Bluetooth Mesh Network Enabled
- TAP Technology – NFC Programmable
- QR Code Programmable
- Tunable White Technology (3000K to 5000K)
- Wattage Adjustable
- 0-10v dim to off

Construction:

- Housing – Code-Gauge Cold-Rolled Steel
- Optics – Acrylic Lens



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical and Light Specifications

- Input Voltage: 120-277VAC
- Adjustable Power: 10-25 Watts, 25-45Watts
- Input Current @ 120V: 0.102 Amps
- Input Current @ 240V: 0.051 Amps
- Input Current @ 277V: 0.044 Amps
- THD: <10%
- Power Factor:>0.99
- Operating Temperature: -4 ~ 122°F
- Kelvin Tunable (3000K to 5000K)
- Color Rendering Index (CRI): >82
- Rated Life: >80,000 Hours

KELVIN
TUNEABLE

ADJUSTABLE
WATTAGE

Ordering Guide:

Example Part Number: **ESL-SPE-521-14-2545W-3050K**

ESL	-	SPE	-	521	-		-		-	3050
ESL		SERIES		TYPE		LENGTH		WATTAGE		KELVIN
				521 (FLat Panel)		14 (1x4) 22 (2x2) 24 (2x4)		1025 (10 to 25W) 2545 (25 to 45W)		3050 (3000K to 5000K)

Catalog Data:

SERIES	LENGTH	WATTS	KELVIN LUMEN OUTPUT			
			3000K	3500K	4000K	5000K
521 - FLAT PANEL - 1025W	1x4	10W	1,300	1,326	1,339	1,365
	2x2	15W	1,950	1,989	2,008	2,047
		25W	3,250	3,315	3,348	3,413
521 - FLAT PANEL - 2545W	1x4	25W	3,250	3,315	3,348	3,413
	2x2	35W	4,550	4,641	4,687	4,778
	2x4	45W	5,850	5,967	6,026	6,143

Dimensions:

SERIES	L	H	DEPTH
521 - FLAT PANEL - 1x4	47.8"	11.9"	1.7"
521 - FLAT PANEL - 2x2	23.7"	23.7"	1.7"
521 - FLAT PANEL - 2x4	47.8"	23.7"	1.7"

