

### Key Features & Benefits:

- Ballast Compatible & Line Voltage
- Double or Single Ended Power
- Food Safety Rated
- Up to 121 Lumens per Watt
- Internal Aluminum Heat Sink
- PET Housing
- Shatterproof Design



Project: \_\_\_\_\_ Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Technical Specifications:

Power: 15 Watts  
 Input Voltage: 100-277 VAC  
 Lumen Output: Up to 1,802 Lumens  
 Efficacy (lm/W): Up to 121 Lumens per Watt  
 Kelvin: 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Housing Material: UL Fire Retardant PET  
 Rated Life (hrs): 50,000 Hours  
 Base Type: G13  
 Tube Dimensions (ØxL): 1.27" x 47.7"  
 Tube Weight (lbs): 0.5 Pounds



### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	QPL CODE
ESL-T8PBC-15W-F135	15W	1,727	116	3500K	>82	PSA2CGX8
ESL-T8PBC-15W-F140	15W	1,765	118	4000K	>82	PSR9YMYF
ESL-T8PBC-15W-F150	15W	1,802	121	5000K	>82	PX8CW72T

### Ordering Guide:

Example Part Number: **ESL-T8PBC-15W-F1**

<b>ESL</b>	-	<b>T8</b>	<b>PBC</b>	-	<b>15W</b>	-	<b>F</b>	<b>1</b>	
ESL		T8	PBC		WATTS		LENS	GENERATION	KELVIN
		T8 Tube	Ballast Compatible		5W (15 Watts)		F (Frosted)	1 (1st Generation)	35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)