

Key Features & Benefits:

- Ballast Compatible & Line Voltage
- Double or Single Ended Power
- Food Safety Rated
- Up to 142 Lumens per Watt
- Internal Aluminum Heat Sink
- PET Housing
- Shatterproof Design



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Technical Specifications:

Power: 9 Watts
 Input Voltage: 100-277 VAC
 Lumen Output: Up to 1,271 Lumens
 Efficacy (lm/W): Up to 142 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Housing Material: UL Fire Retardant PET
 Rated Life (hrs): 50,000 Hours
 Base Type: G13
 Tube Dimensions (ØxL): 1.27" x 23.8"
 Tube Weight (lbs): 0.2 Pounds



Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	CRI	QPL CODE
ESL-T8PBC-9W-F135	9W	1,193	133	3500K	>82	P52GMFME
ESL-T8PBC-9W-F140	9W	1,219	136	4000K	>82	PE2UJ7GC
ESL-T8PBC-9W-F150	9W	1,271	142	5000K	>82	PF4Q3WUZ

Ordering Guide:

Example Part Number: **ESL-T8PBC-9W-F135**

ESL	-	T8	PBC	-	9W	-	F	1	9
ESL		T8	PBC		WATTS		LENS	GENERATION	KELVIN
		T8 Tube	Ballast Compatible		9W (9 Watts)		F (Frosted)	1 (1st Generation)	35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)