



# LED 8' STRIP RETROFIT SERIES



Ti - 8SRK - 60 Watts

PAGE 1 OF 2

### Key Features & Benefits:

- Extremely Quick installation
  - No Rewiring Necessary
  - No Tombstones
  - Quick Connect Technology
- Available in 2', 4' and 8' Lengths
  - 88 Available Configurations
  - 3000K, 3500K, 4000K, and 5000K Available in Ti Series
  - 4000K and 5000K available in TiHO Series

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Technical Data:

#### Light Specifications:

Total Kit Lumens: Up to 8,474 Lumens  
 Efficacy (lm/W): Up to 138 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 80,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Driver Output: Quad Output  
 Output Power: 60 Watts  
 Input Current @ 120V: 0.512 Amps  
 Input Current @ 240V: 0.256 Amps  
 Input Current @ 277V: 0.221 Amps  
 Total Harmonic Distortion (THD): < 10%  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

| ITEM#                    | WATTS | TOTAL KIT LUMENS | EFFICACY (lm/W) | KELVIN |
|--------------------------|-------|------------------|-----------------|--------|
| ESL-Ti-8SRK-S-60W-4L-F30 | 60W   | 8,345            | 136             | 3000K  |
| ESL-Ti-8SRK-S-60W-4L-F35 | 60W   | 8,345            | 136             | 3500K  |
| ESL-Ti-8SRK-S-60W-4L-F40 | 60W   | 8,409            | 137             | 4000K  |
| ESL-Ti-8SRK-S-60W-4L-F50 | 60W   | 8,474            | 138             | 5000K  |

\* Made in the USA option available upon request

Copyright © 2023 ESL Vision, LLC. All rights reserved. Rev: 06/22/2023

### Ordering Guide:

|            |   |           |   |                          |   |          |   |  |   |              |   |             |   |  |   |         |
|------------|---|-----------|---|--------------------------|---|----------|---|--|---|--------------|---|-------------|---|--|---|---------|
| <b>ESL</b> | - | <b>Ti</b> | - | <b>8SRK</b>              | - | <b>S</b> | - | <b>60W</b>   | - | <b>4L</b>    | - | <b>F</b>    | - |  | - |         |
| ESL        |   | TYPE      |   | SERIES                   |   | CLASS    |   | WATTS  |   | Ti           |   | LENS        |   | KELVIN   |   | OPTIONS |
|            |   | Ti Series |   | 8SRK (8' Strip Retrofit) |   | S        |   | 52W (52 Watts)<br>60W (60 Watts)<br>72W (72 Watts)<br>88W (88 Watts) |   | 4L (Four Ti) |   | F (Frosted) |   | 30 (3000 Kelvin)<br>35 (3500 Kelvin)<br>40 (4000 Kelvin)<br>50 (5000 Kelvin) |   |         |

### Alternate 8' Ti Strip Kit Options:



2L Output

### What's Included:

- (4) LED Ti Bar
- (1) LED Driver
- (8) Ti Clips
- (1) Strip Retrofit Plate
- (1) UL1598C Certification Label

### Options (Add as Suffix):

ESL-EMG-2DC-9W  
ESL-4OCC-LDD  
ESL-REM-100

Emergency Back Up, DC, 9 Watt, External Battery  
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

