



LED F313 SERIES

Ti - F313 - 26 Watts



PAGE 1 OF 2

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 3,110 Lumens
 Efficacy (lm/W): Up to 126 Lumens per Watt
 Kelvin: 3,000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 26W
 Input Current @ 120V: 0.217 Amps
 Input Current @ 240V: 0.108 Amps
 Input Current @ 277V: 0.093 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-TI-F313-S-26W-F30	26W	3,026	123	3000K
ESL-TI-F313-S-26W-F35	26W	3,047	124	3500K
ESL-TI-F313-S-26W-F40	26W	3,068	124	4000K
ESL-TI-F313-S-26W-F50	26W	3,110	126	5000K

Ordering Guide:

ESL	Ti	F313	S	26W	F		
ESL	TYPE	SERIES	CLASS	WATTS	LENS	KELVIN	OPTIONS
	Ti Series	F313	S	26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	

Example Part Number: ESL-TI-F313-S-26W-F30

Options (Add as Suffix):

ESL-EMG-FDC-30W	Emergency Back Up, DC, 30 Watt
ESL-EMG-2DC-9W	Emergency Back Up, DC, 9 Watt, External Battery
ESL-4OCC-LDD	Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
ESL-REM-100	Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

