

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Light Specifications:

Lumen Output: Up to 5,056 Lumens  
 Efficacy (lm/W): Up to 120 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >80,000 Hours

### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 44W  
 Dimming: 1-10V  
 Input Current @ 120V: 0.367 Amps  
 Input Current @ 240V: 0.183 Amps  
 Input Current @ 277V: 0.159 Amps  
 THD: <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-Ti-F314-S-44W-F30	44W	4,743	112	3000K
ESL-Ti-F314-S-44W-F35	44W	4,821	114	3500K
ESL-Ti-F314-S-44W-F40	44W	4,900	116	4000K
ESL-Ti-F314-S-44W-F50	44W	5,056	120	5000K

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>F314</b>	-	<b>S</b>	-	<b>44W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		F314		S		26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

### Options (Add as Suffix):

ESL-EMG-2DC-9W  
ESL-4OCC-LDD  
ESL-REM-100

Emergency Back Up, DC, 9 Watt, External Battery  
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v  
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

