

### Key Features & Benefits:

- Extremely Quick Installation:
  - No rewiring necessary
  - No tombstones
  - Does not require access into ceiling plenum or extra junction boxes for installation
  - Quick Connect technology
- Available Kits:
  - 2 Ti Retrofit Plate for lensed troffers
- 18 Total Available Configurations
  - 2,782 to 5,940 lumens
  - 3000K, 3500K, 4000K, and 5000K available in Ti Series
  - 4000K and 5000K available in TiHO Series
- Material
  - Single piece design with pre-drilled holes allowing quick and easy installation
  - Die-formed and embossed code 22 gauge steel
  - High reflectance, baked white enamel finish
- Long Life
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Control Options
  - Photocell
  - Occupancy
- Emergency Capable



Project: \_\_\_\_\_ Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Technical Data:

#### Light Specifications:

Lumen Output: Up to 2,808 Lumens  
 Efficacy (lm/W): Up to 108 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 80,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Driver Output: Dual Output  
 Output Power: 26 Watts  
 Dimming: 0-10v  
 Input Current @ 120V: 0.205 Amps  
 Input Current @ 240V: 0.103 Amps  
 Input Current @ 277V: 0.089 Amps  
 Total Harmonic Distortion (THD): <10%  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	TOTAL KIT LUMENS	EFFICACY (lm/W)	KELVIN
ESL-Ti-PK14-S-26W-2L-F30	26W	2,782	107	3000K
ESL-Ti-PK14-S-26W-2L-F35	26W	2,808	108	3500K
ESL-Ti-PK14-S-26W-2L-F40	26W	2,808	108	4000K
ESL-Ti-PK14-S-26W-2L-F50	26W	2,808	108	5000K

### Ordering Guide:

<b>ESL</b>	<b>Ti</b>	<b>PK14</b>	<b>S</b>	<b>26W</b>	<b>2L</b>	<b>F</b>		
ESL	TYPE	SERIES	CLASS	WATTS	Ti	LENS	KELVIN	OPTIONS
	Ti Series	PK14 (1'x4' Plate Kit)	S	26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)	2L (Two Ti)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	

### Options (Add as Suffix):

- |                 |   |
|-----------------|---|
| ESL-EMG-FDC-30W | Emergency Back Up, DC, 30 Watt                                      |
| ESL-EMG-2DC-9W  | Emergency Back Up, DC, 9 Watt, External Battery                     |
| ESL-4OCC-LDD    | Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v |
| ESL-REM-100     | Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC       |

### What's Included:

- (2) LED Ti Bar
- (1) LED Driver
- (4) Ti Mounting Clips
- (1) Retrofit Plate
- (4) Self Tapping Screw
- (1) UL1598C Certification Label

### Dimensions:

