

Performance Overview:

Wattage: 25 Watts
 Lumen Output: Up to 2,600 Lumens
 Efficacy (lm/W): Up to 104 Lumens
 Kelvin: 4000K, 5000K
 CRI: >70



Project: _____ Date: _____
 Catalog #: _____
 Notes: _____



Key Features & Benefits:

- Built-in 120V Photocell
- Mounting Options:
 - (1) 1/2" Threaded knockout on bottom
 - j-Box Mount Location on Back
- Suitable for Wet Locations
- 10 Year Limited Warranty



Ordering Guide:

ESL	WP	25W	3	
ESL	TYPE	WATTS	GENERATION	KELVIN
	WP (Wall Pack)	25W	3 (3rd Generation)	40 (4000 Kelvin) 50 (5000 Kelvin)



†Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

Product Specifications:

Optical:

- Precision Engineered Optical Lens
- Consistent Uniformity
- Impact Resistant
- UV Protection

Construction:

- Die Cast Housing
- High Performance Heat Sink
- Weathertight LED Driver Housing
- Continuous Gasket Seal
- Low Profile Light Weight Design
- Housing is Completely Sealed and is Suitable for Hose Down Applications.

Electrical:

Input Power: 25 Watts

Power Factor: @120V: 0.99 / @277V: 0.95

Input Voltage: 120-277 VAC

Input Current @120V: 0.208 Amps

Input Current @277V: 0.09 Amps

Total Harmonic Distortion (THD):

THD @120V: 9.7%

THD @277V: 9.7%

Operating Temperature: -40°F to 104°F (-40°C to 40°C)

Life Span: 50,000 Hours

Weight: 2.7 Lbs

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-WP-25W-340	25W	2,500	100	4000K	PLTT63234IFM
ESL-WP-25W-350	25W	2,600	104	5000K	PLBVVQY3TWUM