

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Light Specifications:

Lumen Output: Up to 2,268 Lumens  
 Efficacy (lm/W): Up to 127 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >80,000 Hours

### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 18W  
 Dimming: 1-10V  
 Input Current @ 120V: 0.148 Amps  
 Input Current @ 240V: 0.074 Amps  
 Input Current @ 277V: 0.064 Amps  
 THD: <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F304-S-18W-F30	18W	2,111	120	3000K	PUNF5DVY
ESL-Ti-F304-S-18W-F35	18W	2,150	121	3500K	PKRAMU1M
ESL-Ti-F304-S-18W-F40	18W	2,189	123	4000K	P7FO7RGX
ESL-Ti-F304-S-18W-F50	18W	2,268	127	5000K	PIXJL57

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>F304</b>	-	<b>S</b>	-	<b>18W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		F304		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

### Options (Add as Suffix):

ESL-EMG-5DC-10W  
ESL-4OCC-LDD  
ESL-REM-100

Emergency Backup, 1250 Lumens, 90 min backup, 120-277 VAC, Factory Installed  
Occupancy and Photocell Sensor, 0-10v Dimming, 8'-20' Mounting  
Hand Held Remote

### Dimensions:

