

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 2,684 Lumens
 Efficacy (lm/W): Up to 124 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 22W
 Dimming: 1-10V
 Input Current @ 120V: 0.18 Amps
 Input Current @ 240V: 0.09 Amps
 Input Current @ 277V: 0.078 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F304-S-22W-F30	22W	2,486	115	3000K	P652K4ZB
ESL-Ti-F304-S-22W-F35	22W	2,536	117	3500K	P8261O37
ESL-Ti-F304-S-22W-F40	22W	2,585	119	4000K	P70B04A1
ESL-Ti-F304-S-22W-F50	22W	2,684	124	5000K	PAAPGICV

Ordering Guide:

ESL	-	Ti	-	F304	-	S	-	22W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		F304		S		13W (13 Watts) 15W (15 Watts) 18W (18 Watts) 22W (22 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Options (Add as Suffix):

ESL-EMG-5DC-10W
ESL-4OCC-LDD
ESL-REM-100

Emergency Backup, 1250 Lumens, 90 min backup, 120-277 VAC, Factory Installed
Occupancy and Photocell Sensor, 0-10v Dimming, 8'-20' Mounting
Hand Held Remote

Dimensions:

