

Key Features & Benefits:

- Extremely Quick installation
 - No rewiring necessary
 - No tombstones
 - Quick Connect Technology
- Available in 2', 4' and 8' Lengths
 - 3000K, 3500K, 4000K, and 5000K available in Ti Series
 - 4000K and 5000K available in TiHO Series
- 16 Available 2' Configurations
 - 1,310 to 3,432 Lumens

Project: _____ Date: _____

Catalog #: _____

Notes: _____



Technical Data:

Light Specifications:

Total Kit Lumens: Up to 1,400 Lumens
 Efficacy (lm/W): Up to 140 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Single Output
 Output Power: 10 Watts
 Input Current @ 120V: 0.083 Amps
 Input Current @ 240V: 0.041 Amps
 Input Current @ 277V: 0.036 Amps
 Total Harmonic Distortion (THD): < 10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	TOTAL KIT LUMENS	EFFICACY (lm/W)	KELVIN
ESL-Ti-2SRK-S-10W-1L-F30	10W	1,310	131	3000K
ESL-Ti-2SRK-S-10W-1L-F35	10W	1,330	133	3500K
ESL-Ti-2SRK-S-10W-1L-F40	10W	1,360	136	4000K
ESL-Ti-2SRK-S-10W-1L-F50	10W	1,400	140	5000K

* Made in the USA option available upon request

Ordering Guide:

ESL	Ti	2SRK	S	10W	1L	F		
ESL	TYPE	SERIES	CLASS	WATTS	Ti	LENS	KELVIN	OPTIONS
	Ti Series	2SRK (2' Strip Retrofit)	S	10W (10 Watts) 13W (13 Watts)	1L (One Ti)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)	

Alternate 2' Ti Strip Kit Options:



2L Output

Options (Add as Suffix):

ESL-EMG-FDC-30W
ESL-EMG-2DC-9W
ESL-4OCC-LDD
ESL-REM-100

Emergency Back Up, DC, 30 Watt
Emergency Back Up, DC, 9 Watt, External Battery
Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

What's Included:

- (1) LED Ti Bar
- (1) LED Driver
- (2) Ti Clips
- (1) Strip Retrofit Plate
- (1) UL1598C Certification Label

Dimensions:

