

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Safe - No Glass to Shatter

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Electrical Data:

Light Specifications:

Lumen Output: Up to 3,720 Lumens
 Efficacy (lm/W): Up to 155 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >50,000 Hours
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 24W
 Input Current @ 120V: 0.2 Amps
 Input Current @ 240V: 0.1 Amps
 Input Current @ 277V: 0.087 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F314-S-24W-F35	24W	3,672	153	3500K
ESL-ID-F314-S-24W-F40	24W	3,672	153	4000K
ESL-ID-F314-S-24W-F50	24W	3,720	155	5000K

Ordering Guide:

ESL	-	ID	-	F314	-	S	-	24W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		ID Series		F314		S		24W (24 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Options (Add as Suffix):

ESL-4OCC-LDD
ESL-REM-100

Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

