

Product Features:

- Robust Housing with Stainless Steel Hardware
- Ip67 Rated with NSF Certification
- Wide Operating Temperature Range of -40°F to 122°F
- 0–10v Driver with 12v Aux
- Optional Integrated Stand Alone or Network Controls for Maximum Energy Savings



Ordering Guide:

ESLX			1			
ESLX	TYPE	WATTS	GENERATION	KELVIN	LENS	OPTIONS
	VP2 (2FT VAPOR) VP4 (4FT VAPOR) VP8 (8FT VAPOR)	20W (20W - 2FT) 25W (25W - 4FT) 45W (45W - 4FT) 65W (65W - 8FT)	1 (1ST GENERATION)	40 (4000K) 50 (5000K)	BLANK (FROSTED)	FACTORY INSTALLED

Options (factory installed):

EMERGENCY BBU:
EM5 (EMG BBU 5W OUTPUT CLOSED LEAD WIRING)
EM9 (EMG BBU 9W OUTPUT OPEN TERMINAL WIRING)
SENSORS:
OCC (OCCUPANCY SENSOR)
CONTROLS:
KRPP2 (KONEX RELAY MODULE TRANSMITTER/RCVR)

Accessories (field installed):

LENS:
ESL-VP2-ELENS-FR (2' VAPOR TIGHT FROSTED REPLACEMENT LENS)
ESL-VP4-ELENS-FR (4' VAPOR TIGHT FROSTED REPLACEMENT LENS)
ESL-VP8-ELENS-FR (8' VAPOR TIGHT FROSTED REPLACEMENT LENS)
MOUNTS:
ESL-VP-SFMK (VAPOR TIGHT SURFACE MOUNT KIT)
CONTROLS:
ESL-REM100 (HAND HELD REMOTE TO PROGRAM OCC)
CONNECTORS:
ESL-ACCS-VP-CONN (TANDEM WIRING CONNECTOR)

Product Specifications:

Construction:

Fully gasketed, white polycarbonate housing with captive stainless steel latches and mounting hardware. NSF splash zones.

Optical:

UV Stabilized, high impact translucent lens for maximum light output.

Catalog Data:

4FT	ITEM#	WATTS PER LAMP	LUMENS PER LAMP	EFFICACY (LM/W)	KELVIN
	ESL-VP4-25W-140	25W	3,250	130	4000K
	ESL-VP4-25W-150	25W	3,250	130	5000K

4FT	ITEM#	WATTS PER LAMP	LUMENS PER LAMP	EFFICACY (LM/W)	KELVIN
	ESL-VP4-45W-140	45W	5,850	130	4000K
	ESL-VP4-45W-150	45W	5,850	130	5000K

8FT	ITEM#	WATTS PER LAMP	LUMENS PER LAMP	EFFICACY (LM/W)	KELVIN
	ESL-VP8-65W-140	65W	8,450	130	4000K
	ESL-VP8-65W-150	65W	8,450	130	5000K

Dimensions:

