

Illumination:

- Ultra bright, energy efficient, long life Red or Green LEDs.

Electrical:

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery).
- Charge rate/power “ON” LED indicator light and magnetic test switch for mandated code compliance testing.
- 4.8V long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting:

- Die-cast mounting brackets provided for surface wall-mount installation.
- Pre-installed conduit hub for conduit and pendant-mount installations.

Housing:

- Housing is reinforced polycarbonate construction in gray finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- EZ snap-out Chevron directional indicators.

Options:

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.



Catalog Data:

Sample Part Number: HLWLEZU1RGEM

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	BATTERY	OPTIONS
HLWLEZU	1	Single	R Red	(blank)	AC-Only
	2	Double	G Green	EM NiCd Battery	SDT TP Self-Diagnostics ¹ Tamper-Proof

¹ Available in EM units only.

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Warranty / Listing:

Five year warranty on all electronics and housing. Batteries pro-rated for five years. Meets UL924, UL844, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. IP66 rated for Ingress Protection. Rated for Class 1, Division 2, Groups A, B, C, & D. Certified to CEC under Title 20 Regulations. UL listed for wet locations (-20°C – 50°C).

Electrical Information:

CATALOG NUMBER	INPUT WATTS (W)		INPUT AMPS (A)	
	120	277	120V	277V
HLWLEZU-RED/GREEN/EM/SDT	3.0	3.0	0.03	0.02

Dimensions:

