

Illumination:

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.
- Long-life, energy efficient Red or Green LED EXIT sign illumination.

Electrical:

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery).
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing.
- 6V/12V maintenance-free, rechargeable NiCd battery (12W, 15W models).
- 6V/12V maintenance-free, rechargeable sealed lead acid battery (28W model).
- Offers 4.8W, 7.8W, 20.8W of remote capacity (6V/12V DC output) standard on the 12W, 15W and 28W models.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting:

- Universal knockout pattern on back provided with gasket for watertight seal for back mount.
- Polycarbonate mounting canopy included for top or end mount.

Housing:

- Housing is reinforced polycarbonate construction in white or black finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- Knockout's provided for conduit feed applications. EZ snap-out Chevron directional indicators.

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Options:

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- CW: Optional internal heater and battery blanket for extreme cold temperature applications (-20°C – 50°C).
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- NH: No lamp heads attached to the unit enabling it to be used as a remote capable EXIT sign.

Warranty / Listing:

Five year warranty on all electronics and housing. Batteries prorated for two (lead acid) / five (NiCd) years. Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. IP66 rated for Ingress protection. NEMA4X rated. UL certified for use in food service operations.



Catalog Data:

Sample Part Number: INDCWLEZU1R615B

¹ Available only in 15W & 28W models.

² Available only in 12W models.

³ Available only in 12W & 15W models.

MODEL	No. of FACES	LETTER COLOR		VOLTAGE		WATTAGE		HOUSING COLOR		OPTIONS		
INDCWLEZU	1	Single ¹	R	Red	6	6 volts	12	12 watts	W	White	SDT	Self-Diagnostics
	2	Double ²	G	Green	12	12 volts	15	15 watts	B	Black	CW	Cold Weather ³
							28	28 watts			TP	Tamper-Proof
											NH	No Heads

Project: _____ Date: _____
Catalog #: _____
Notes: _____

Dimensions:

