

Illumination:

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

Electrical:

- Dual 120/277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery).
- Charge rate/power “ON” LED indicator light and magnetic test switch for mandated code compliance testing.
- 6V/12V maintenance-free, rechargeable NiCd battery (15W models).
- 6V/12V maintenance-free, rechargeable sealed lead acid battery (36W and 54W models).
- Offers 7.8Wh, 28.8Wh, 46.8Wh of remote capacity (6V/12V DC output) standard on the 15W, 36W and 54W models.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours (36 hours on the 54W model).

Mounting:

- Universal knockout pattern on back provided with gasket for watertight seal for back mount.
- Suitable for wall mount.

Housing:

- Housing is reinforced polycarbonate construction in white or black finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- Knockout’s provided for conduit feed applications.



Catalog Data:

Sample Part Number: INDEMR16G15B

¹ Available only in 15W models.

MODEL	BATTERY VOLTAGE		WATTAGE		HOUSING COLOR		OPTIONS	
INDEMR16	6	6 Volt	15	15 watts	W	White	SDT	Self-Diagnostics
	12	12 Volt	36	36 watts	B	Black	CW	Cold Weather ¹
			54	54 watts			TP	Tamper-proof

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Options:

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- CW: Optional internal heater and battery blanket for extreme cold temperature applications (-25°C – 50°C).
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

Warranty / Listing:

Five year warranty on all electronics and housing. Batteries prorated for two (lead acid) / five (NiCd) years. Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. IP66 rated for Ingress protection. NEMA4X rated. UL certified for use in food service operations. UL listed for wet locations (0°C – 50°C on 15W and 10°C – 40°C on 36W / 54W models).

Dimensions:

