

Performance Summary:

- Wattage: 170
- Lumens: Up to 23120 Lumens
- Efficacy: Up to 137 Lumens per Watt
- Kelvin: 4000K & 5000K
- CRI: >82
- Mounting: Ships with V-Hooks and (2) 6' chain kits
 - Comes Standard with Shorting Cap for Easy Field Installation of Occupancy Sensors
- Weight: 11.24lbs



Project: _____ Date: _____

Catalog #: _____

Notes: _____



TUNABLE
WHITE



Product Specifications:

Optical:

- Semi-diffused PMMA lens for glare control

Construction:

- High performance aluminum heat sink

Mounting:

- Ships with V-Hooks and (2) 6' chain kits
- Other mounting available in accessories

Electrical:

- Input Voltage: 120-277 VAC
- Power Factor @120 VAC - 0.98%, @277 VAC - 0.90%
- THD @120 VAC <9%, @277 VAC <9%
- Operating Temperature: -4°F to 131°F (-20°C to 55°C)
- 12V AUX
- 0-10V Dimmable
- Konex Network Sensors Available

Ordering Guide:

ESL	-	LHB	-	2	-	170W	-	1	4050	-	
ESL		TYPE		SIZE		WATTAGE		GENERATION	KELVIN		OPTIONS*
		LHB (Lensed High Bay)		2 (2'x2')					4000/5000K		FACTORY INSTALLED

*Options (Factory Installed)

Emergency BBU:
EM18 (Emergency BBU, 90 min Backup, 120-277 VAC, Factory Installed)
Cord Sets:
CS3W6P (Cord Set, 3 Conductor, 18 Gauge, White, 6 Foot Length, Straight Blade Plug)
CS3B6P (Cord Set, 3 Conductor, 18 Gauge, Black, 6 Foot Length, Straight Blade Plug)
CS3B6TL5 (Cord Set, 3 Conductor, 18 Gauge, Black, 6 Foot Length, Twist lock, Nema L5-15 - 120V)
CS3B6TL6 (Cord Set, 3 Conductor, 18 Gauge, Black, 6 Foot Length, Twist lock, Nema L6-15 - 240V)
CS3B6TL7 (Cord Set, 3 Conductor, 18 Gauge, Black, 6 Foot Length, Twist lock, Nema L7-15 - 277V)