


Key Features & Benefits:

- Wet Location Approved
- Omnidirectional
- Rated for Fully Enclosed Fixtures



Technical Specifications:

- Power: 46 Watts
- Lumen Output: Up to 5,715 Lumens
- Efficacy (lm/W): Up to 124 Lumens per Watt
- Kelvin: 3000K, 4000K, 5000K
- CRI: >80
- Input Voltage: 120-277 VAC
- Life Span: 50,000 Hours
- Beam Angle: 300°
- Dimensions(ØxH): 3.66" x 10.18"
- Weight(lbs): 2.2 lbs
- Base Type: E39/E26
- Operating Temperature: -4 ~ 149°F (-20 ~ 65°C)
- Power Factor: >0.95
- Total Harmonic Distortion (THD): < 20%



Project: _____

Date: _____

Catalog #: _____

Notes: _____



No Fans



No Noise



No Bugs

ITEM #	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-CL-46W-230	46W	5,155	112	3000K
ESL-CL-46W-240	46W	5,430	118	4000K
ESL-CL-46W-250	46W	5,715	124	5000K

*2700K and 5700K available upon request

Ordering Guide:

Example Part Number: **ESL-CL-46W-230S**

ESL	-	CL	-	46W	-	2	-		-	
ESL		TYPE		WATTS		GENERATION		KELVIN		BASE
		CL		46W (46 Watts)		2 (2nd Generation)		30 (3000K) 40 (4000K) 50 (5000K)		S (E26) M (E39)

Additional Options:

2
OPTIONS

ESL-SP-277 (Surge Protector up to 277 VAC)

