

Performance Overview:



Wattage: 18 Watts
 Lumen Output: Up to 2,724 Lumens
 Efficacy (lm/W): Up to 157 Lumens
 Kelvin: 3000K, 3500K, 4000K, 5000K
 CRI: >80

Project: _____ Date: _____
 Catalog #: _____
 Notes: _____



Key Features & Benefits:

- Glass Construction with Shatterproof Coating
- > 220° Beam Spread
- Double Ended or Single Ended Wiring
- Integral Driver (Isolated)



Product Specifications:

Optical:

- Wide beam angle - >220°
- Starting time <1.0s, Instant on, no delay

Construction:

- Seamless, uniform Glass tube design with frosted or shatterproof cover for choice
- Aluminum alloy end cap
- Glass with PET Coating
- Tube Weight (lbs): 0.4 lbs

Electrical:

- Input Voltage: 120-277 VAC
- Input Current @120V: 0.15 Amps
- Input Current @208V: 0.09 Amps
- Input Current @240V: 0.08 Amps
- Input Current @277V: 0.06 Amps
- Power Factor: >0.9
- THD: <20%
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)
- Life Span: 50,000 Hours
- Base Type: G13

Ordering Guide:

ESL	-	T8	-	GLV	-	18W	-	F	3	
ESL		TUBE		TYPE		WATTS		LENS	GENERATION	KELVIN
				GLV (Glass Line Voltage)		18W		F (Frosted)	3 (3rd Generation)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

†Not All Part Numbers DLC Qualified. For a Complete Listing Please Consult the DLC Qualified Products List (QPL).

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-T8-GLV-18W-F330	18W	2,551	145	3000K	PL2RS4ES6L9V
ESL-T8-GLV-18W-F335	18W	2,717	155	3500K	PL6W4LMZE52H
ESL-T8-GLV-18W-F340	18W	2,719	156	4000K	PL9DOC3KQ583
ESL-T8-GLV-18W-F350	18W	2,724	157	5000K	PL8DJ16JATX9

Installation:

